

Skid-Steer Loaders / S650 Skid-Steer Loader

Specifications & Options

 Standard  Optional  N/A Not Applicable

Units US

Bobcat S650

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	74 hp
Turbocharged Engine	<input checked="" type="checkbox"/>

Performance

Rated Operating Capacity (ISO)	2,690 lb
Tipping Load	5380 lb
Operating Weight	8061 lb
Travel Speed	7.1 mph
Travel Speed (2-speed option)	12.3 mph

Capacities

Fuel Tank	23.9 gal
-----------	----------

Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	23 gal/min
Auxiliary High Flow	30.5 gal/min

Dimension

Length	136.8 in
Length without Attachment	108.4 in
Length with Standard Bucket	136.8 in
Width	72.1 in
Width (with bucket)	74 in
Height	81.3 in
Height with Operator Cab	81.3 in
Height to Bucket Hinge Pin	124 in
Reach @ Maximum Height	31.5 in
Turning Radius	82.9 in
Wheelbase	45.3 in

Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Adjustable Seat	<input type="checkbox"/>
Backup Alarm	<input type="checkbox"/>
BICS System (Interlock)	<input type="checkbox"/>
Cab Enclosure	<input checked="" type="checkbox"/>
Sound Option	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	<input type="checkbox"/>
Parking Brake	<input type="checkbox"/>
Radio	<input checked="" type="checkbox"/>
Rear Window	<input type="checkbox"/>
Top Window	<input type="checkbox"/>
Lift-Arm Support	<input type="checkbox"/>
Seat Belt	<input type="checkbox"/>
Suspension Seat	<input type="checkbox"/>
Two Speed Travel	<input checked="" type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Engine Shutdown	<input type="checkbox"/>
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Spark Arrestor Muffler	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Power Bob-Tach	<input checked="" type="checkbox"/>
ACS (Switchable Controls)	<input checked="" type="checkbox"/>
Ride Control	<input checked="" type="checkbox"/>
Rear Hydraulics	<input checked="" type="checkbox"/>



Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.